



Features:

1. Day and Night
2. 28 Unit Ir Led (Option)
3. Aluminum Housing
4. Weatherproof

Specification

Model	FOS-602IR
Image Pick-up Device	Two 1/3" SONY CCD, COLOR 420 and B/W 600 TV Lines
Number of Pixels	NTSC: 510(H)x492(V); PAL: 500(H)x582(V)
Scanning System	NTSC: 525 Lines,60 Field/sec; PAL: 525 Lines 50 Field/sec
Horizontal Resolution	420 TV Lines
Usable Illumination	0 Lux At Night (LED ON)
IR Series Distance	50 Meter (28 Led On)
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control
Gamma Characterlstic	0.45
Video Output	1.0Vp-p 75 ohm
S/N Ratio	≥48dB (AGC Off)
Electronic Shutter Time	On: NTSC1/60~1/100,000Sec, PAL 1/50~1/100,000Sec; Off: NTSC 1/60 Sec, PAL 1/50 Sec
Operation Temperature	-10°C~+50°C RH95% Max
Storage Temperature	-20°C~+60°C RH95% Max
Cable	BNC/DC JACK
Lens	F: 12.0mm
BLC	Open
Power Supply	DC12V±10%

